





Doc.no:	S-002_06
Version:	V1.0
Last updated:	2024.03.19


A – Dimensions: [mm]



B – suggested footprint: [mm]



C – Schematic



D – Electrical Properties:

Properties	Test conditions	Value	Unit	Tol.
Inductance	10.0KHz 0.3VAC	2.2	mH	Min.
Turns ratio		1 : 1 : 1		±1%
Saturation current		57	Amps	
DC Resistance			mΩ	Max
Insulation voltage	4500Vac	50Hz/3mA		

E – Application Properties:

Properties		Value	Unit
Input voltage	Ui	-	V (DC)
Output voltage	Uo	-	V
Output current	Io	-	A
Auxiliary voltage	Uaux	-	V
Switching frequency	fswitch	65 – 500	kHz

E – General information:

It is recommended that the temperature of the part does not exceed +125°C under worse case conditions.

- Storage Temperature: - 20°C to 60 °C
- Operating Temperature: - 40°C to 125 °C
- Test conditions of Electrical Properties: 20°C, 40% RH

REV.	Description/Reason	Date
A	First version	2026.05.21

HIPOWER ELECTRONICS (NINGBO) CO., LTD
恒博尔电源（宁波）有限公司
www.trafopsu.com 0086 (574) 8667 1366
Email: sales@trafopsu.com 0086 135 0669 7578

Item Description	CM Choke 3x2.2mH 20A	
Hipower P/N	612055	
Revision	Designed by	Approved by
A	HAY	JEP